

#10-R-2218362

1438620
G29-003565

SPECIFICATIONS

ELECTRIC LIFT TRUCK SIT DOWN RIDER

- 1) **Capacity:** 3,500 pounds
- 2) **Dimensions:**
 - Maximum fork height cannot be less than 172"
 - Maximum overall height cannot exceed 82"
 - Maximum width 40.5"
 - Maximum length to fork face 76.2"
 - Minimum tilt: 5 degrees front/5 degrees back
 - Maximum overhead guard height cannot exceed 82"
- 3) **Features:**
 - Power, 36 volt
 - Forks, minimum 42" long, 4" wide, 1.5" thick, standard pallet
 - Side shift function
 - 48" load backrest
 - Smooth cushion rubber tires
 - Tilt steering column with steering wheel
 - Seat with operator restraint system
 - Hour meter, indicator lights, on-board diagnostics
 - Mast 3 stage full free lift
 - Lift interrupt battery discharge indicator
 - Front drive tires minimum 18" rear, steer tires minimum 14"
 - Programmable performance modes
 - Automatic parking brake
 - Directional control forward/reverse selector
 - Backup alarm 87db
 - Load center 24"
- 4) **Battery:**
 - One (1) new 36 volt battery of correct size for unit
 - Lead acid
 - 17 plate battery 18-85RC17 rapid charge with single point watering system
 - Minimum 680 amp hour
 - Battery shall be installed and fully charged upon delivery
- 5) **Charger:**
 - Must be matched to battery voltage and amp hour capacity
 - Charger shall operate on 208AC 3 phase voltage
 - Charger shall be high frequency
- 6) **Successful bidder must have a factory authorized service shop within 100 miles of Montgomery, Alabama, and provide on-site warranty and repair service with a four (4) hour response time during normal business days.**